

Problem 1

- 1) The duration of the GI could be equal to T_p (one rectangle) or $2.5T_p$ (two rectangles plus the interval).
With $T_G=T_p$ and $A=1$, $V_{pMIN}=8.9\mu V$; with $T_G=2.5T_p$ and $A=1$, $V_{pMIN}=7\mu V$.
Therefore, the best choice is collecting the whole signal.
- 2) A whitening filter to get only white noise is necessary. The filter also acts on the signal producing 4 exponential signals corresponding to the 4 edges (two rising and two falling ones); the time constant is 318ns. With an ideal optimum filter we'd obtain $V_{pMIN}=35\mu V$.
- 3) At the output of the whitening filter of point 2) we obtain a noise spectrum consisting of white noise and $1/f$ noise with $f_c=10kHz$. The ideal optimum filter already provides a high pass filtering action thanks to the subtraction of exponential signals with opposite polarity. The additional contribution of $1/f$ noise can be estimated considering an upper bandwidth limitation equal to $1/(4T_c)$ and a lower bandwidth limitation equal to $1/(2\pi T_p)$. The overall noise is therefore $\sqrt{4S_V f_c \ln\left(\frac{\pi T_p}{2T_c}\right)} \approx 31\mu V$. As a result, the SNR is reduced by almost 9% with respect to point 2 (and $V_{pMIN}=38.5\mu V$).

Problem 2

- 1) The basic configuration of the detector-preamplifier assembly consists of an equivalent current generator with a capacitor in parallel both modeling the p-i-n photodiode. The signal is collected by means of a resistor in parallel to the generator, followed by a preamplifier.
Reasonable values for the parameters are:
 - Photodiode:
 - o PDE(800nm)=55% ($R=0.1$, $t_n=200nm$, $t_d=10\mu m$) [Resulting $S_D=0.35A/W$]
 - o $C=1pF$
 - Preamplifier:
 - o Gain 1 (for simplicity)
 - o $\sqrt{S_V} = \frac{4nV}{\sqrt{Hz}}$
 - o $\sqrt{S_I} = \frac{1pA}{\sqrt{Hz}}$
 - Resistor:
 - o $1k\Omega$

The phototube has an extremely low efficiency at 800nm (at most around 2% with a S25 photocathode).

- 2) It is convenient to use a simple low pass filter with a pole at 100Hz to avoid signal loss. In this case the noise equivalent bandwidth is $\pi/2 * f_p$ (detailed theory is required here).
The minimum transmitted power that can be measured is $P_{MIN}=206pW$.
Photosensor with internal gain: we could use an APD (not a PMT because of poor PDE at 800nm).
Reasonable APD (additional) parameters:
 - o $G = 100$
 - o $F = 2$
 - o $I_D=0.15fA$

The dominant noise contribution is still the electronics noise but its impact on the SNR is reduced by the gain. $P_{MIN}=1.42pW$

- 3) The best solution is to modulate and demodulate the signal with a square-wave reference at 100kHz. (detailed theory on square wave modulation and demodulation is required here).

P_{MIN} is the same of point 2.